

BEST AVAILABLE COPY

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 03-252172

(43)Date of publication of application : 11.11.1991

(51)Int.Cl.

H01L 31/10

(21)Application number : 02-050564

(71)Applicant : SANYO ELECTRIC CO LTD

(22)Date of filing : 28.02.1990

(72)Inventor : NOGUCHI SHIGERU

ISHIDA SATOSHI

IWATA HIROSHI

SANO KEIICHI


NAKAYAMA SHOICHIRO

## (54) PHOTSENSOR AND MANUFACTURE THEREOF

## (57)Abstract:

PURPOSE: To easily obtain a photosensor having high sensitivity without loss of sensitivity at a short wavelength side by arranging pectinated collector electrodes made of a polycrystalline region on one main surface of a translucent substrate, and forming a thin film photosemiconductor layer directly on one main surface of the board by covering the electrode.

CONSTITUTION: A P-type a-SiC layer 41 is formed on an insulating transparent supporting board 1, and recrystallized by laser annealing to form pectinated collector electrode made of polycrystalline SiC. Then, an i-type a-Si layer 42, an n-type a-Si layer 43 are laminated on the layer 41, and a semiconductor film 4 having a pin junction is formed. Thereafter, the film 4 is patterned except a region necessary as a photosensor. Then, a metal film 45 is formed on the film 4. Then, lead electrodes 46 from a back electrode 5 and a collector electrode 10 are formed.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office